

ROM - ECOPACT

High pressure skid-mounted jetting unit



**UNDERGROUND
TECHNICAL SERVICES LTD**

For all your Drain Equipment needs



ROM ECOPACT

The ROM ECOPACT is a high pressure sewer cleaning machine with a whole new look. ROM has broken new ground by paying attention to both the functionality and the design of the machine.

The ROM ECOPACT has a hose guiding system in the shape of an extendable operating arm. Never before could a sewer cleaning hose be reeled in and out so easily! Thanks to the special hose tensioning mechanism, the hose can be neatly reeled in without any effort. The operating arm also ensures that you can work sideways to the vehicle without any problems.

No sewer or well is out of reach for you anymore!



TYPICAL ROM ECOPACT CHARACTERISTICS

ECONOMIC

The ECOPACT is light (from 500 kg), making it suitable for medium-sized commercial vehicles such as the VW Transporter and the MB Vito. The standard diesel engine ensures low fuel consumption and a low machine/hour price.

COMPACT

The design of the ECOPACT is extremely compact. The polyester front panel can easily be removed for service to the machine. Daily inspection is possible via the service hatch in the front panel. The ECOPACT also has a ROM heat exchanger for perfect machine temperature control.

USERFRIENDLY

The ECOPACT invites you to work with it, all the components are positioned at ergonomic height. The ECOPACT also has an easy-to-use stainless steel operating panel.

DESIGN

The front panel has been designed by an industrial designer and gives the ECOPACT an even more professional look. The panel comes in metallic grey as standard, but can be ordered in any colour for an additional charge. The frame has been fully hot dip galvanised and has large stainless steel drip trays under the reels.

HOSE GUIDING SYSTEM

The ECOPACT has a new hose guiding system in the shape of an extendable operating arm. The knowledge and experience built up over the past 25 years has been used in this revolutionary development.



The economic skid-mounted sewer jetting unit



The ROM ECOPACT is available in the following versions:

Article number	0243	0244	0245
Name	ROM ECOPACT 200/60	ROM ECOPACT 150/75	ROM ECOPACT 200/72 PTO
Engine	32hp Kubota diesel	32hp Kubota diesel	PTO
Pump	Speck 200 bar - 60l/min	Speck 150 bar- 75l/min	Speck 200 bar- 72l/min
Tank capacity	600l.		
Empty weight	approx. 500kg	approx. 500kg	approx. 500kg
Dimensions (l x w x h)	1290 x 1200 x 1200mm.		
HP sewer jetting hose	80m. 1/2" (ND 13)		



High pressure reel, incl. hose guiding system



Service hatch in front panel; perfect for daily inspection



Pressure gauge



Pressure regulator



Automatically closing water filter with filter



Storz coupling for quick filling of the water tank (optional)

Options



Remote control Professional Yellow



Work light on magnetic bracket



2nd high pressure reel



120m. instead of a 80m. 1/2"
ROM sewer jetting hose



Venturi type ejector



Lining of the vehicle

- Remote control Professional Yellow
- Cable remote control with hydraulic 2x2-way system
- Unwinding on off via the remote control
- Work light on magnetic bracket
- Automatic starting of the diesel engine on the control panel and the remote control
- Spraypainted in your company's or municipality's colour
- 2nd HP reel, whereby the filling reel is omitted.
Equipped with ROM 3-way/unloader combination system
- 120m. instead of a 80m. 1/2" ROM sewer jetting hose
- Eagle silence drive
- Venturi type ejector in combination with 66mm. Storz filling connection incl. 10m hose, strainer and override switch
- Extra 600l or 1000l water tank
- Dry run protection
- ROM pulsation system
- Lining of the vehicle

Underground Technical Services LTD

Humphreystown, Blessington
Co. Wicklow, Ireland

Tel : + 353 (0) 45 867790
Fax : + 353 (0) 45 867921

E-mail : info@utsltd.ie
Internet : www.utsltd.ie

