

ROM - VAC PICK-UP UNIT

Vacuum unit

 **UNDERGROUND**
TECHNICAL SERVICES LTD
For all your Drain Equipment needs



ROM VAC PICK-UP

The ROM VAC pick-up units are intended for the simple emptying of grease traps, septic tanks and cesspits in places with awkward access such as schoolyards and shopping centres.

The ROM VAC pick-up units are also suitable for the removal of excess water after flooding problems.

The ROM VAC pick-up units are available in different versions (600l. - 2000l. tanks). The VAC units offer mobility and flexibility. A perfect opportunity to expand your activities.



TYPICAL ROM VAC PICK-UP CHARACTERISTICS

SAFETY

The vacuum system consists of: a floating ball valve in the tank (over suction protection), moisture trap with sight glass, vacuum valve (set to ± 0.6 bar) and combined oil separator/exhaust silencer. This ensures you can work safely.

DURABLE

The vacuum tank is robust and very durable because it has been completely galvanised.

PICK-UP SYSTEM

De ROM VAC is placed on a steel frame onto which fork-lift tubes are connected. Thanks to this, you can easily place your ROM VAC on a trailer or a pick-up truck.

DESIGN

The ROM VAC has been designed according to a new concept, where attention was devoted to both functionality and design of the machine. The design bonnet is optional.



The ROM VAC PICK-UP is available in the following versions:

Article number	0318	0319	0321	0322	0323
Name	ROM VAC 600	ROM VAC 1000	ROM VAC 1200	ROM VAC 1600	ROM VAC 2000
Engine	9hp Honda	9hp Honda	13hp Honda	13hp Honda	13hp Honda
Pump	MEC 2000	MEC 2000	MEC 4000	MEC 4000	MEC 4000
Tank capacity	600l	1000l	1200l	1600l	2000l
Empty weight	approx. 490kg	approx. 540kg	approx. 600kg	approx. 650kg	approx. 705kg
Dimensions	(L) 1.70x1.20x1.40m (W) 1.20x1.70x1.40m	(L) 2.10x1.30x1.50m (W) 1.55x1.80x1.50m	(L) 2.39x1.30x1.50m (W) 1.76x1.89x1.50m	(L) 2.25x1.50x1.62m (W) 1.64x2.04x1.62m	(L) 2.57x1.50x1.62m (W) 1.96x2.04x1.62m
Vacuum hose	2m. ND70				



Userfriendly operation



Durable powerful vacuum pump



Several Honda engines (9, 11, 13hp)



Combined oil separator/ noise insulation



Suction hose connection & clamp for secure closing of the vacuum tank



Pressure gauge and safety valve

Options



Design bonnet with hinged cover



Suction hose reel



Active carbon filter for air filtration

- The engine/pump combination can be fixed either on the front or the left-hand side so that a long/narrow or short/wide machine originates
- The engine/pump combination can be provided with a design engine bonnet with hinged cover
- Suction hose reel (suction hose not included) is not available on the VAC 600
- 2nd connection with 18m. suction hose and plug with suction tube. Storage on two hooks and suction tube in holder
- Vacuum tank painted in a colour of your choice
- Active carbon filter for air filtration
- Extra exhaust silencer on the petrol engine

Underground Technical Services LTD

Humphreystown, Blessington
Co. Wicklow, Ireland

Tel : + 353 (0) 45 867790
Fax : + 353 (0) 45 867921

E-mail : info@utsltd.ie
Internet : www.utsltd.ie

